

SPECIAL SPECIFICATION**3120****Asphalt-Stabilized Flexible Base**

- 1. Description.** Construct a mixture of asphalt material and flexible-base material to be used as a base and surfacing for roadways, driveways, intersections and other areas shown on the plans or as directed.
- 2. Materials.** Furnish the quantity of asphalt material to be used per cubic yard or ton of flexible base as shown on the plans.

Furnish asphalt material meeting the requirements of Item 300, "Asphalts, Oils and Emulsions" of the type and grade shown on the plans.

Furnish flexible base of the type and grade as shown on the plans.
- 3. Construction.** Mix the asphalt material and the flexible base by any approved method. Construct the asphalt-stabilized-flexible-base mixture at the locations and to the lines and grades established on the plans or directed.
- 4. Measurement.** This Item will be measured by the cubic yard or by the ton of material in vehicles as delivered on the road.
- 5. Payment.** The work performed and the materials furnished in accordance with this Item and measured as provided under "Measurement" will be paid for at the unit price bid for "Asphalt-Stabilized Flexible Base". This price shall be full compensation for furnishing all required materials; for all royalty and freight involved; for all mixing, hauling, spreading, shaping, sprinkling, compacting and furnishing of the material as specified; and for all manipulation, labor, tools, equipment and incidentals.