
Special Provision to Item 6

Control of Materials



Item 6, "Control of Materials" of the Standard Specifications is amended with respect to the clauses cited below. No other clauses or requirements of this Item are waived or changed.

Article 6.9. Recycled Materials, is voided and replaced by the following:

The Department will not allow hazardous wastes, as defined in 30 TAC 335, proposed for recycling. Use nonhazardous recyclable materials (NRMs) only if the Specification for the Item does not disallow or restrict use. Determine if NRMs are regulated under 30 TAC 312, 330, 332, 334, or 335, and comply with all general prohibitions and requirements. Use NRMs in accordance with DMS-11000, "Evaluating and Using Nonhazardous Recyclable Materials Guidelines," and furnish all documentation required by that Specification.

Article 6.10. Hazardous Materials, is voided and replaced by the following:

Use materials that are free of hazardous materials as defined in Item 1, "Abbreviations and Definitions." Notify the Engineer immediately when a visual observation or odor indicates that materials in required material sources or on sites owned or controlled by the Department may contain hazardous materials. Except in the case of Section 10.1.1.1, "Cleaning and Painting Steel" below, the Department is responsible for testing and removing or disposing of hazardous materials not introduced by the Contractor on sites owned or controlled by the Department as indicated below. The plans will indicate locations where paint on steel is suspected to contain hazardous materials and where regulated asbestos containing materials have been found. The Engineer may suspend work wholly or in part during the testing, removal, or disposition of hazardous materials on sites owned or controlled by the Department, except in the case of Section 10.1.1.1.

When a visual observation or odor indicates that materials delivered to the work locations by the Contractor may contain hazardous materials, have an approved commercial laboratory test the materials for contamination. Remove, remediate, and dispose of any of these materials found to be contaminated. Testing, removal, and disposition of hazardous materials introduced onto the work locations by the Contractor will be at the Contractor's expense. Working day charges will not be suspended and extensions of working days will not be granted for activities related to handling hazardous material delivered by the Contractor.

10.1. Painted Steel Requirements. As shown on the plans, existing paint on steel may contain hazardous materials. Perform work in accordance with the following:

10.1.1. Removing Paint from Steel.

10.1.1.1. Cleaning and Painting Steel. For contracts that are primarily for painting existing steel, perform the work in accordance with Item 446, "Field Cleaning and Painting Steel."

10.1.1.2. Other Contracts. For all other projects when an existing paint must be removed to perform other work, perform paint removal work in accordance with Item 446, "Field Cleaning and Painting Steel" unless the paint is shown or determined to contain hazardous materials. If the paint is shown or determined to contain hazardous materials, the Department will provide for a separate contractor to remove paint prior to or during the Contract to allow dismantling of the steel for the Contractor's salvaging, reuse, or recycling or where paint must be removed to perform other work. For steel that is dismantled by unbolting, no paint stripping will be required. Use care to not damage existing paint. When dismantling is performed using flame or saw-cutting methods to remove steel elements coated with paint containing hazardous materials, the plans will show stripping locations. Coordinate with the separate contractor for stripping work to be performed during the Contract.

10.1.2. Removal and Disposal of Painted Steel. For Contracts where painted steel is to be removed and disposed of by the Contractor, painted steel may be reused or disposed of at a steel recycling or smelting facility. If the paint is shown or determined

to contain hazardous materials, maintain and make available to the Engineer invoices and other records showing the reuse owner or for recycling, records obtained from the recycling or smelting facility showing the received weight of the steel and the facility name. Painted steel to be retained by the Department will be shown on the plans.

10.2. Asbestos Requirements. The plans will indicate locations or elements where asbestos containing materials (ACM) have been found. At these locations or at locations where previously unknown ACM has been found, the Department will arrange for abatement by a separate contractor during the Contract. For work at these locations, notify the Engineer of proposed dates of demolition or removal of structural elements with ACM at least 60 days before work is to begin to allow the Department sufficient time to abate the asbestos.

When the work by a separate contractor for removal of paint or asbestos abatement is to be performed during the Contract, provide traffic control as shown on the plans and coordinate and cooperate with the separate contractor. Continue other work detailed in the plans not directly involved in the paint removal or asbestos abatement work. Coordinate with the Department the timing of the separate contractor's work in advance in order to allow the Department to schedule work with the separate contractor. Work for the traffic control and other work will not be paid for directly but will be subsidiary to pertinent items.