
Special Provision to Item 712

Cleaning and Sealing Joints and Cracks (Asphalt Concrete)



Item 712, "Cleaning and Sealing Joints and Cracks (Asphalt Concrete)" of the Standard Specifications is amended with respect to the clauses cited below. No other clauses or requirements of this Item are waived or changed.

Article 712.4., "Work Methods," is supplemented by the following:

When the number of cracks is so great that crack sealing in the described manner is impractical, the area must be squeegee sealed. When all cracks in the area have been cleaned, the crack sealing material must be applied and the excess must be squeegeed over the area between the cracks. Areas to be squeegee sealed will be determined and marked by the Engineer. All polymer modified emulsion or hot poured rubber squeegee sealed areas must be covered immediately with a light coating of fine aggregate.

Article 712.5., "Measurement," is voided and replaced by the following:

This Item will be measured by the foot, gallon, pound, lane mile or square yard. Shoulders wider than 6 ft. are considered additional lanes.

Article 712.6., "Payment," is voided and replaced by the following:

The work performed and materials furnished in accordance with this Item and measured as provided under "Measurement" will be paid for at the unit price bid for "Joint and Crack Sealing," of the sealant material specified; "Joint and Crack Sealing (Squeegee)," and "Joint and Crack Routing and Sealing" of the sealant material specified. This price will be full compensation for routing, cleaning and sealing all joints and cracks, for placing all materials including fine aggregate and for all labor, equipment, tools and incidentals.