
Special Specification 2014

Asphalt-Stabilized Flexible Base



1. DESCRIPTION

Construct a mixture of asphalt material and flexible base material to be used as a base and surfacing on off-system roadways, intersections, driveways, turnouts, and other areas shown on the plans or as directed by the Engineer.

2. MATERIALS

Furnish the quantity of asphalt material to be used per cubic yard or ton of flexible base material as shown on the plans.

Furnish asphalt material meeting the requirements of Item 300, "Asphalts, Oils, and Emulsions," of the type and grade shown on the plans.

Furnish flexible base material of the type and grade shown on the plans.

3. EQUIPMENT

Provide machinery, tools, and equipment necessary for proper execution of the work.

Provide rollers in accordance with Item 210, "Rolling," for each type of roller used for compaction.

4. CONSTRUCTION

Mix the asphalt material and the flexible base material by any approved method. Construct the asphalt-stabilized flexible base mixture at the locations and to the lines and grades established on the plans or as directed by the Engineer.

5. MEASUREMENT

This item will be measured by the cubic yard or by the ton of material in vehicles as delivered on the road.

6. PAYMENT

The work performed and the materials furnished in accordance with this Item and measured as provided under "Measurement" will be paid for at the unit price bid "Asphalt-Stabilized Flexible Base." This price shall be full compensation for furnishing all required materials; for all royalty and freight involved; for mixing, hauling, spreading, shaping, sprinkling, and compacting material as specified; and for all manipulation, labor, tools, equipment, and incidentals.