

---

# Special Specification 4152

## Dimensional Quarried Limestone

---



### 1. DESCRIPTION

- 1.1. This Item will govern the installation of terracing and trail shoulders composed of approved quarried limestone blocks.

---

### 2. MATERIALS

- 2.1. **Roughly Squared Stone.** The Contractor will source the stone from a local quarry. The stone will be sound, durable limestone, free from structural defects, uniform in color and texture, and will be clean of earth, clay, oil or other foreign substances. Stones will be of the type and dimensions shown on the plans.
- 2.2. **Excavation and Backfill for Structures.** Excavation and backfill for this item will comply with Item 400, "Excavation and Backfill for Structures."

---

### 3. CONSTRUCTION METHODS

- 3.1. **General.** The Contractor will be responsible for verifying all dimensions incidental to this work and will promptly report any discrepancies to the Engineer.

The stone will be installed in accordance with these specifications, in conformity with the form, dimensions, and design shown on plans, and to the lines and grades established by the Engineer.

---

### 4. MEASUREMENT

- 4.1. This Item will be measured by the linear foot complete in place. Only accepted work will be included, and the dimensions used for measurement will be those shown on the plans or ordered in writing by the Engineer.

---

### 5. PAYMENT

- 5.1 The work performed and materials furnished in accordance with this Item and measured as provided under "Measurement" will be paid for at the unit price bid for "Dimensional Quarried Limestone". This price will be full compensation for furnishing and hauling all materials, for all freight involved, for preparing and placing all materials, and for all labor, tools, equipment, anchoring appurtenances, and incidentals necessary to complete the work.