
Special Specification 8025

Asphaltic Concrete Patching Material (Bagged) (Materials Only)



1. DESCRIPTION

This Specification governs for crushed stone asphaltic concrete intended primarily as a cool- to cold-weather bagged patching mix for maintenance. The mixture must remain workable for 6 mo. from the day of delivery and have good adhesion to wet surfaces. The length of satisfactory storage and the lowest temperature at which it can be used will vary according to the type and grade of asphaltic binder specified.

2. MATERIALS

- 2.1. **Material Producer List (MPL).** The Flexible Pavements Section of the Materials and Tests Division (MTD/FP) maintains the MPL of all materials conforming to the requirements of this Specification. Materials appearing on the MPL, entitled "Asphaltic Concrete Patching Material (Stockpile Storage or Bagged)," require no further testing unless deemed necessary by the Engineer. Use of pre-qualified product does not relieve the Contractor of the responsibility to provide product that meets this Specification. Materials not appearing on the MPL may not be provided.
- 2.2. **All Season Pre-Coated Patching Mixture (ASPPM).** When called for in the plans, provide an ASPPM as listed on the MPL under category 'ASPPM Grade 4'.
- 2.3. **Water Activated Patching Material.** When called for on the plans, provide a patching material with water activated binder. All water activated patching materials shall be listed on the MPL under category 'Non-Volatile Mixture (NVM) Grade 4'.

3. MEASUREMENT AND PAYMENT

Material will be measured by the bag. Bags must weigh 60-lbs per bag.

Payment will be made for the type specified. This price is full compensation for furnishing materials, loading, hauling, delivery of materials, furnishing scales and labor for weighing and measuring if needed, and equipment, labor, tools, and incidentals.