

anty of any the conversic No warre lity for by hat se his star TxDOT he he is

403								
ed t s	Vertical Pile Loads							
) <i>S</i>	Tons/Pile							
SB15	4SB12	4SB15						
46	26	28						
51	29	31						
57	32	34						
62	34	37						
67		40						
71		43						

construction ioint

1'-0" 2' (Typ)

SECTION B-B

TABLE OF ESTIMATED	6						
QUANTITIES							

Bar	No.	Size	Length (5)		Weight (5)			
			4SB12	45	B15	4SB12	4SB15	
Α		6	#11	33'-3"	3.	3'-3"	1,060	1,060
Ε		4	#4	2'-2"	2'-2"		6	6
F		10	#4	6'-4"		6'-4"	43	43
Н		2	#5	31'-10"	31	-10"	66	66
L		6	#6	4'-0"		4'-0''	36	36
S		44	#4	9'-4"		9'-4''	275	275
U		4	#6	7'-1"	7'-1"		43	43
V		31	#5	7'-4"	7'-10"		237	253
W	Η1	8	#6	5'-8''	5'-8''		68	68
W	Н2	8	#6	6'-11"	6'-11''		83	83
W	U	12	#4	1'-8"	1'-8"		14	14
W	V	28	#5	3'-10"	4'-1''		112	119
Re	Reinforcing Steel					Lb	2,043	2,066
CI	CI "C" Conc (Abut)					СҮ	10.4	10.8

(1) Top of cap elevations are based on section depths shown on Span Details.

(2) See Span Details for "Y".

- (3) Increase as required to maintain 3" from finished grade.
- (4) See Bridge Layout to determine if approach slab is present.
- 5 See Bridge Layout for beam type used in the superstructure.
- (6) Quantities shown are for one abutment only (with approach slab). Without approach slab, add 1.2 CY Class "C" concrete and 66 Lb reinforcing steel for 2 additional Bars H.
- (7) $\frac{1}{2}$ " preformed bituminous fiber material between slab beam and earwall. Bond to earwall with an approved adhesive. Cast inside face of earwall perpendicular to cap. (Typ)

GENERAL NOTES:

Designed according to AASHTO LRFD Bridge Design Specifications Designed for a normal embankment header slope

- of 3:1 and a maximum span length of 50 feet. See Bridge Layout for header slope and foundation
- type, size, and length.
- type, size, and length. See Common Foundation Details (FD) standard sheet for all foundation details and notes. See Concrete Riprap (CRR) standard sheet or Stone Riprap (SRR) standard sheet for riprap attachment
- details, if applicable. See applicable rail details for rail anchorage in wingwalls. These abutment details may be used with standard
- SPSB-30 only.

Cover dimensions are clear dimensions, unless noted otherwise. Reinforcing bar dimensions shown are out-to-out of bar

MATERIAL NOTES: Provide Class C concrete (f'c = 3,600 psi). Provide Class C (HPC) concrete if shown elsewhere in the plans. Provide Grade 60 reinforcing steel.

