DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

LOC NO.	TCP PHASE	PLAN SHEET NUMBER (optional)	LOCATION DESCRIPTION OF LOCATION. (CROSS STREET, GORE, LEFT OR RIGHT, ETC)	STA APPROX. STATION NUMBER OF CC	TEST LEVEL TL2=<=45MPH TL3=ALL SPEEDS	DIRECTION OF TRAFFIC (UNI/BI)	FOUNDATION PAD			BACKUP SUPPORT (OBJECT BEING SHIELDED)			AVAILABLE SITE LENGTH	CRASH CUSHION										ENTER REF# FOR EACH STANDARD TO BE CONSIDERED AT EACH INSTALL LOCATION
							PROPOSED MATERIAL	PROPOSED THICKNESS	IS THE EXISTING SURFACE SUFFICIENT TO ANCHOR THE CRASH CUSHION? (YES/NO)	DESCRIPTION	WIDTH	HEIGHT				MOVE / RESET		L	L	R	R	S	S	
							WHAT MATERIAL WILL THE CRASH CUSHION BE ANCHORED TO? CONCRETE , ASPHALT, ETC			SINGLE SLOPE, F-SHAPE, BRIDGE RAIL TYPE	WIDEST WIDTH OF OBJECT BEING SHIELDED	HEIGHT OF OBJECT BEING SHIELDED	LONGITUDINAL SPACE AVAILABLE TO INSTALL CRASH CUSHION	INSTALL	REMOVE	MOVE/ RESET	FROM LOC. #	N	W	N	W	N	W	SEE TABLE
1	Phase 1	121	IH 35 @ imaginary rd	456+32	TL3	Bi	Asph	2"	Yes	F-Shape	24"	32"	32'	X									22, 24
2	Phase 2	125	Temp Exit ramp@Exit 127	457+42	TL3	Uni	Conc	8"	Yes	LPCB	28"	20"	25'	X									22
3	Perm	125	IH 35 @ imaginary 2 rd	457+32	TL3	Bi	Conc	8"	Yes	T551	17"	32"	30'	X					X				10, 12, 15
4	Phase2	126	IH35@NW corner blank crk brg	458+18	TL3	Uni	Conc	8"	Yes	T221	12"	32"	>50'		X							X	
5	Phase2	132	median barrier end	460+80	TL3	Bi	Conc	10"	Yes	Single Slope	24"	42"	23'			X	2					X	
6	Perm	133	IH 35 @ blah blah rd	466+84	TL3	Bi	Conc	Standard	Yes	Single Slope	24"	42"	>50'	X				X					1, 3, 5
7	Phase2	133	Temp Exit ramp@Exit 127	457+42	TL3	Uni	Conc	Standard	Yes	Single Slope	24"	42"	>50'		X							X	
8	Perm	133	IH 35 @ blah blah rd	466+84	TL3	Uni	Conc	Standard	Yes	Single Slope x2	48"	42"	>50'	X					X				2, 4, 6
9	Perm	135	IH35 @100 acre underpass	476+80	TL3	Bi	Conc	Standard	No	Bridge Column	36"	42"	42"	X					X				4, 6

Example

LEGEND:
L=LOW MAINTENANCE
R=REUSABLE
S=SACRIFICIAL
N=NARROW
W=WIDE

1. If all standard sheets for selected category are not relevant an explanation is required under item 545 in general notes.

FOR DEFINITIONS SEE THE "CRASH CUSHION CATEGORIZATION CHART.PDF" AT THE DESIGN DIVISION (ROADWAY STANDARDS) WEBSITE. USE QUICK LINKS TO ACCESS ATTENUATORS / CRASH CUSHIONS SECTION.
http://www.dot.state.tx.us/insdtdot/orgchart/cmd/cserve/standard/rdwylse.htm

Ref. #	Low Mainenance	Ref. #	Reusable	Ref. #	Sacrificial
1	QGELITE(M10)(N)	10	QGUARD(M10)(N)	19	SSCC
2	QGELITE(M10)(W)	11	QG(M)(W)	20	CATCB(1)
3	REACT(M)	12	TAU(M)(N)	21	MATT(1)
4	REACT(W)	13	TAU-M(W)	22	ABSORB(M)
5	SMTC(N)	14	TRACC(W)	23	SLEDMINI
6	SMTC(W)	15	DELTACC	24	SLED
7	TAU-XR(N)	16	SMARTPOD	25	VIA(SFPM)
8	TAU-XR(W)	17		26	
9		18		27	

VERSION 11-20-2025

CRASH CUSHION SUMMARY SHEET

FILE: ccss example.dgn	DN: CES	CK: KM	CK:
© TxDOT Nov 2025	CONT	SECT	JOB	HIGHWAY
REVISIONS				
	DIST	COUNTY	SHEET NO.